



CROWN™

Technical Data Sheet

AIRFOAM™



Foam Booster & Brush Lubricant for Tunnel, Friction, & Self-Serve Car Washes

Low viscosity, high foaming detergent designed for use in friction car washes. Provides lubricity to bristles and cloth while generating thick, long-lasting foam. May be applied through foaming equipment or through direct feed to bristle or cloth. Enhances customer appeal. Pumps easily in all temperatures. pH neutral.

Directions for Use

Apply this product at a dilution rate of 120:1 - 240:1 (approximately 1-2 oz per gallon of water). Adjust as needed to achieve desired foam level.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Red Liquid
Odor	Cherry
pH (1% solution, 22°C)	<8.0
Foaming	Very High
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.51±0.1
Stability Range	50-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

82405
82415
82430
82455

Packaging

5 gal. pail
15 gal. drum
30 gal. drum
55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com

