

Technical Data Sheet



Hustle™

Industrial Steam Cleaner and Pressure Wash Detergent

Professional quality pressure wash detergent for removing dirt and grime from all types of industrial surfaces, including walls, equipment, floors, machinery, etc. Contains a very powerful blend of solvents, surfactants, and alkalis in addition to special emulsifiers for rapid soil penetration and removal. Produces abundant foam for increased dwell time on vertical surfaces. An ideal product for most pressure washing applications. Designed to deliver effective performance where other products fail. Highly dilutable and economical to use.

Directions for Use

Prior to use, test product in an inconspicuous area to assure compatibility with surface. Wear appropriate safety equipment at all times.

Pressure Washing: Using low pressure, apply this product at a feed rate of 2-8 ounces per gallon of hot water (16-64:1) depending on soil levels. For best results, apply to a dry surface--do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow several minutes contact time for detergent to penetrate and dissolve soils. Using hot water under high pressure (1,000 psi or higher), rinse surface completely. Do not allow solutions to dry on surface. For spot removal or very heavy grease or soil accumulation, use at full strength.

Manual Washing: For brush and bucket washing, dilute this product at 1-2 ounces per gallon of hot water (60-100:1). Apply using a mop, sponge or scrub brush. Allow several minutes contact time. Agitate to improve soil removal, then rinse completely.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Blue Liquid
Odor	Characteristic
pH (1% solution, 22°C)	>11.5
Foaming	High
Flash Point	None
Bulk Density (lbs/gal, 22°C)	9.10 ±0.1
Stability Range	50-100°F
Free Alkalinity (as Na ₂ O)	Very High
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content (as P)	None

Product Number

91255

Packaging

55 gal. drum



4701 W. 136th Street • Crestwood, IL 60445
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com

