

LEGACY™

High Solids Premium Floor Finish for High or Low Speed Applications

A premium quality all speed finish which provides excellent gloss and durability on resilient tile floors. This product is a 24% solids finish which contains metal interlock, multi-coatable polymer which forms a clear, touch, long-wearing shine. Recommended for use on floors made of linoleum, vinyl, asbestos, terrazzo, rubber, concrete, sealed wood and unglazed ceramic. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, ect.

Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. Strip old finish from floor rinse completely and allow to air dry. Apply in this, even coats using a rayon mop or lamb wool pad. For optimum gloss and durability, apply 5 coats or more, allowing at least 30 minutes drying time between coats. Floor may be machine buffed to a higher gloss if desired. Coverage = approximately 2,500 sq. ft./gal.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's can be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	White Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<9.5
Foaming	None
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.63 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na2O)	None
Solubility (in H2O, 22°C)	100%
Phosphate Content	None

Product Number

43541
43505

Packaging

4x1 gal. case
5 gal. pail