

Technical Data Sheet



MetalSolve™

Heavy Duty Low Foaming Metal Cleaner-Degreaser

A versatile detergent for removing grease, oil and other soils from ferrous (iron, steel, copper and titanium) and non-ferrous (aluminum, zinc and galvanized) metals. Ideal for parts washing in all types of immersion and recirculating tanks, as well as spray wash caninets. Safe for use on most types of rubber and elastomer.

Directions for Use

For most applications, dilute 2-12 ounces of this product per gallon of hot water. Apply solution at an operating temperature range of 160°-180°F. Change solution frequently to assure best results. Operate machine according to manufacturer's instructions. Thoroughly rinse all parts with water after cleaning or subsequent treatment. For best results, use fresh detergent solution in hot, soft water with maximum agitation.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Tan Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<11.5
Foaming	Low
Flash Point	None
Bulk Density (lbs/gal, 22°C)	9.08 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	Low
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content (as P)	None

Product Number

91305
91355

Packaging

5 gal. pail
55 gal. drum



4701 W. 136th Street • Crestwood, IL 60445
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com

